

10 GAUGE SOILD COPPER WIRE W/ DOUBLE CHECK 600V INSULATION CORPORATION STOP -VALVE & FITTING CONTINUOUS COLOR. (NORMALLY OPEN) LOCATING WIRE ALONG MAIN. USE PRE-FILLED DRI-SPLICE WIRE CONNECTORS W/CRIMP SLEEVE FOR ALL WIRE 45° 30° YOKE BAR SPLICING. (SPEARS DS-400 or METER APPROVED EQUAL) - CURB STOP AWWA TYPE CC THREADS TYPE "K" FLEXIBLE COPPER OR CTS WATER MAIN POLYETHYLENE TUBING (1" MIN) - SADDLE

NOTES:

- 1. ALL FITTINGS SHALL BE BRASS WITH COMPRESSION/PACK JOINT TYPE CONNECTIONS.
- 2. NO SERVICE LINE SHALL TERMINATE UNDER A DRIVEWAY.
- 3. EACH SERVICE SHALL TERMINATE AT A CURB STOP(S) WHICH SHALL BE BURIED APPROXIMATELY 3" BELOW FINAL GRADE AND SHALL BE CLEARLY MARKED WITH A 2" x 2" x 18" STAKE WITH THE TOP PAINTED BLUE AND MARKED WITH THE NUMBER OF THE LOT(S) TO BE SERVED.
- RECLAIMED WATER SERVICES SHALL BE PAINTED PURPLE (COPPER) OR USE PURPLE COLORED CTS POLYETHYLENE TUBING.
- POTABLE WATER SERVICES SHALL BE PAINTED BLUE (COPPER) OR USE BLUE COLORED CTS POLYETHYLENE TUBING.

WATER SERVICE CONNECTION DETAIL

CITY OF SANFORD

2014-9

FIG. 405